

Price Guide Effective From April 15 , 2024***Thermo Scientific Eutech 1700 Series Bench Meters**
Rapid and consistent laboratory results

1710 pH/mV bench meter measures pH or ORP simultaneously with mV and Temperature

1720 Conductivity bench meter measures conductivity, salinity or TDS simultaneously with temperature

1730 Dissolved oxygen bench meter measures DO as % saturation or concentration in mg/L or ppm simultaneously with temperature

Benefits

- ❖ Easily view 5" display with backlight
- ❖ Save bench space with small meter footprint
- ❖ 500-point data log
- ❖ All data and calibration logs are date and time stamped for GLP/GMP reporting
- ❖ The meter's non-volatile memory preserves settings and data in the event of power loss
- ❖ Interface with computer programs including LIMS, Hyper Terminal, etc.



Order Code	Description	Price (INR)
Waterproof Elite Pocket Testers		
ELITEPH	Elite pH pocket tester with soft case, lanyard and batteries	17100.00
ELITECTSPIN	Elite CTS pin-sensor pocket tester with soft case, lanyard and batteries	17100.00
ELITECTSCUP	Elite CTS cup-sensor pocket tester with soft case, lanyard and batteries	18450.00
ELITEORP	Elite ORP pocket tester with soft case, lanyard and batteries	24300.00
ELITEPCTS	Elite PCTS pocket tester with soft case, lanyard and batteries	29700.00
ELITEPHSPEAR	Elite pH spear pocket tester with lanyard and batteries	39600.00



Accessories		
01X001535	Replacement sensor, ELITEPH	8100.00
01X001538	Replacement sensor, ELITEPHSPEAR	23400.00
01X001524	Replacement sensor, ELITEORP	9900.00
01X001526	Replacement sensor, ELITECTSPIN	7200.00
01X001528	Replacement sensor, ELITECTSCUP	8100.00
01X001530	Replacement sensor, ELITEPCTS	10800.00

Waterproof pH Pocket Testers		
ECOPHTEST1	Waterproof EcoTestr pH 1 tester without ATC, 1 point calibration	7020.00
ECOPHTEST2	Waterproof EcopHTestr 2 tester with ATC; 3 point calibration	7920.00
EXPERTPH	Waterproof Expert pH pocket tester with ATC and temperature display, 3-point calibration, ± 0.1 pH accuracy	8910.00
Waterproof pH Testers		
PHTEST10	Waterproof pHTestr 10 tester with ATC; ± 0.1 pH accuracy	9900.00
PHTEST20	Waterproof pHTestr 20 tester with ATC; ± 0.01 pH accuracy	13500.00
PHTEST30	Waterproof pHTestr 30 Tester with ATC and temperature readout; ± 0.01 pH resolution	17100.00
Waterproof pH Testers with BNC Connector		
PHTEST10BNC	Waterproof pHTestr 10 BNC tester with MTC; BNC connector sensor; ± 0.01 pH resolution (meter only – electrode to be ordered separately)	14400.00
Waterproof pH Spear Testers		
PHSPEAR	Waterproof pHSpear tester with MTC; double-junction spear-tip electrode; ± 0.01 pH accuracy	36000.00





Waterproof ORP / Redox Pocket Testers

ORPTEST10	Waterproof ORPTestr 10 large dual display tester (-999 to +1000 mV)	21600.00
ORPTEST10BNC	Waterproof ORPTestr 10 large dual display tester; BNC connector sensor; (-999 to +1000 mV); (meter only – electrode to be ordered separately)	16100.00

Accessories

PHSENSOR03DJ	Replacement double junction sensor for pHTestr 10, 20, 30	6300.00
PHSENSORBNC	Replacement BNC connector sensor for pHTestr 10BNC and ORPTestr 10BNC	5400.00
PHSENSOR04	Replacement double junction spear-tip electrode for pHSpear	21600.00
ORPSENSORDJ	Replacement double junction sensor for ORPTestr 10	7920.00

Accessories

ECFC7252101B	General purpose plastic-body single junction gel-filled pH combination electrode, 12x90mm, BNC connector, 1m cable length	6750.00
ECFC72521R01B	General purpose plastic-body single junction refillable pH combination electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	11700.00
ECFC7252201B	General purpose plastic-body double junction gel-filled pH combination electrode, 12x90mm, BNC connector, 1m cable length	9900.00
ECFC72522R01B	General purpose plastic-body double junction refillable pH combination electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	14400.00
ECFC7252203B	General purpose plastic-body single junction gel-filled ORP electrode, 12x90mm, BNC connector, 1m cable length	P.O.R
ECFC7960201B	General purpose plastic-body double junction gel-filled ORP electrode, 12x90mm, BNC connector, 1m cable length	P.O.R



Economy pH / ORP / Ion Handheld Meters

ECION602PLUSK	Ion 6+ pH/Ion/ORP meter with single junction pH electrode ECFC7252101B, ATC probe & pH carrying kit set	P.O.R
---------------	---------------------------------------------------------------------------------------------------------	-------

ECPH602PLUSK	pH 6+ pH/ORP meter with single junction pH electrode ECFC7252101B, ATC Probe & pH carrying kit set	P.O.R
--------------	----------------------------------------------------------------------------------------------------	-------

Note: Ion 6+ , pH 6+ & pH 5+ pH Carrying Kit consists of a carrying case with 1 x pH 4.01, pH 7.00 buffer solutions, storage solution and 1 x deionised (rinse) water (60 ml each)



Waterproof pH / ORP / Ion Handheld Meters



ECPHWP15002K	Meter with double-junction pH electrode ECFC7252201B and ATC probe, grip-clip, two AA batteries, hard carry case, pH buffers, storage solution, rinse solution. ORP electrode to be ordered separately	P.O.R
ECPHWP45002K	pH 450-meter kit with double-junction pH electrode ECFC7252201B and ATC Probe, grip-clip, two AA batteries, hard carry case, USB cable, pH buffers, storage solution, rinse solution. ORP electrode and Ion Selective Electrode to be ordered separately	P.O.R

Waterproof pH / ORP / Ion Handheld Meters

ECPHWP62042K	Waterproof CyberScan pH 620 pH/mV/Ion, meter with double junction pH electrode ECFC7252203B, ATC probe, DAS software, power adapter & pH carrying kit set	P.O.R
ECPHWP61042K	Waterproof CyberScan pH 610 pH/mV meter with double junction pH electrode ECFC7252203B, ATC probe, DAS software, power adapter & pH carrying kit set	P.O.R
ECPHWP60042K	Waterproof CyberScan pH 600 pH/mV meter with double junction pH electrode ECFC7252203B, ATC Probe, DAS software, power adapter & pH carrying kit set	P.O.R

Note: pH 620, pH 610 & pH 600 pH carrying kit consists of a carrying case with 1 x pH 4.01, pH 7.00 buffer solutions, storage solution and 1 x deionized (rinse) water (60 ml each)

Accessories

ECPH5TEM01P	ATC probe (for Ion 6+, pH 6+, pH 5+, pH 110 & pH 11 only); 1m cable length	7650.00
PHWPTEM01W	ATC probe (for pH 310, pH 300, PC300 ,PC510, PH 150, CON 150, PH 450, CON 450, PC 450) 1m cable length	12600.00
ECPHWPTM01J	ATC probe (for pH 620, 610, 600, PC650, PD650, PCD650 only); 1m cable length	12600.00
ECPHWPTM03J	ATC probe (for pH 620, 610, 600, PC650, PD650, PCD650 only); 3m cable length	12600.00
ECFC7252101B	General purpose plastic-body single junction gel-filled pH combination electrode, 12x90mm, BNC connector, 1m cable length	6750.00
ECFC7252201B	General purpose plastic-body double Junction gel-filled pH combination electrode, 12x90mm, BNC connector, 1m cable length	9900.00
ECFC7252203B	General purpose plastic-body double Junction gel-filled pH combination electrode, 12x90mm, BNC connector, 3m cable length	P.O.R
60X030130	100 /240VAC SMPS power adapter with US/UK/EUR/Japan plug ,9V,6W, centre +ve (for Cyberscan 11 / 110 / 510/1100 / 2100 series)	4950.00
60X426401	100 /240VAC SMPS power adapter , 9V,6W (150, 450 and 2700 series)	9000.00
01X030132	Universal SMPS,100 /240VAC,9V,6W, centre +ve power adapter with US/UK/EUR/Japan plug (for Cyberscan 600	13500.00



	series)	
AN-270	Dot matrix printer, Brand Antech	36000.00
ECFC72521R01B	General purpose plastic-body single junction refillable pH combination electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	11700.00
ECFC72522R01B	General purpose plastic-body double junction refillable pH combination electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	14400.00
ECFC7252205B	General purpose plastic-body double junction gel-filled pH combination electrode, 12x90mm, BNC connector, 5m cable length	P.O.R
ECFC7352901B	General purpose plastic-body "3-in-1" pH/Temp. combination electrode, 12x90mm, BNC connector, 1m cable length (for pH 5/6, Ion 6, pH 11/110, pH 510 & pH 1100/2100)	11700.00
ECFC7352901W	General purpose plastic-body Gel-Filled "3-in-1" pH/Temp. combination electrode, 12x90mm, BNC and 6 pin connector, 1m cable length (for pH 310, 300, PC300 & PC510)	15300.00
ECFC7352901J	General purpose plastic-body Gel-Filled "3-in-1" pH/Temp. combination electrode, 12x90mm, BNC and 8 pin connector, 1m cable length (for pH 620, 610, 600, PC650, PD650, PCD650 only)	15300.00
ECFG7350401B	General purpose glass-body single junction refillable pH combination electrode, annular ceramic reference junction with protective sensor guard, 12x110mm, BNC connector, 1m cable length & 10ml refilling electrolyte	9990.00
ECFC7960101B	General purpose plastic-body single junction gel-filled ORP electrode, 12x90mm, BNC connector, 1m cable length	P.O.R
ECFC7960201B	General purpose plastic-body double junction gel-filled ORP electrode, 12x90mm, BNC connector, 1m cable length	P.O.R

pH / ORP / Ion Bench Meters

EBPH171003	1710 pH/mV meter with ECFC7252201B double junction gel-filled plastic-body pH electrode, PH5TEMB01P stainless steel ATC temperature probe, electrode stand, PC cable, and universal power adapter	P.O.R
ECPH70042S	pH 700 meter with single junction pH electrode ECFC7252101B, ATC probe PH5TEMB01P, integral electrode holder and 100/240 VAC adapter	P.O.R
ECPH70042S-I	pH 700 meter with indigenous glass pH electrode AN-786-1 , BNC connector, 1m cable length, ATC probe PH5TEMB01P, integral electrode holder and 100/240 VAC adapter	P.O.R
ECPH70042GS	pH 700 meter with glass body, open pore pH electrode EC620131, ATC probe PH5TEMB01P, integral electrode holder and 100/240 VAC adapter	P.O.R
ECION270042GS	Ion 2700 meter with pH electrode (ECFG7370101B), ATC probe (PH5TEMB01P), integral electrode holder, 100/240 VAC adapter, RS232 cable, & pH electrode refill solution. Ion electrodes to be ordered separately	P.O.R
ECPH270042GS	pH 2700 Meter with pH electrode (ECFG7370101B), ATC probe (PH5TEMB01P), integral electrode holder, 100/240 VAC adapter, RS232 cable	P.O.R
ECPH27005E	pH 2700 meter with glass body, open pore pH electrode EC620131, ATC probe PH5TEMB01P, integral electrode holder , 100/240 VAC adapter and RS232 cable	P.O.R



ECPH27005E-P	pH 2700 meter with glass body, open pore pH electrode EC620131, ATC probe PH5TEMB01P, integral electrode holder , 100/240 VAC adapter, RS232 cable and AN-270 dot matrix printer	P.O.R
ECPH51042S-I	pH 510 pH/mV meter with indigenous glass pH electrode AN-786-1 , BNC connector, 1m cable length, indigenous ATC probe , integral electrode holder & power adapter	P.O.R
ECPH51042S	pH 510 pH/mV meter with single junction pH electrode ECFC7252101B, ATC probe , integral electrode holder & power adapter	P.O.R
ECPHTUTOR-I	pH Tutor meter with indigenous glass pH electrode AN-786-1 , BNC connector, 1m cable length, indigenous electrode stand and power adapter. ATC probe to be ordered separately	P.O.R
ECPHTUTOR-D	pH Tutor meter with plastic-body "3-in-1" pH/Temp.(ATC in-built) combination electrode, 12x90mm, BNC connector, 1m cable length, indigenous electrode stand and power adapter	P.O.R
ECPHTUTOR-S	pH Tutor meter with single junction pH electrode ECFC7252101B , 12x90mm, BNC connector, 1m cable length, indigenous electrode stand and power adapter. ATC probe to be ordered separately	P.O.R
ECPHTUTOR-DS	pH Tutor meter with plastic-body "3-in-1" pH/Temp.(ATC in-built) combination electrode, 12x90mm, BNC connector, 1m cable length, integrated electrode stand with swivel arm and power adapter	P.O.R

Accessories		
EC620130	Glass body, refillable, open pore (10ml electrolyte 620-430 included)	P.O.R
ECPH5TEMB01P	ATC probe (for Tutor, Ion 510, pH 510, pH 700, Ion 700, pH 1100, pH 2100, pH 2700, Ion 2700, pH 1710), 1m cable length	8550.00
ECFG7370101B	Glass body double junction Ag/AgCl refillable pH electrode, 12 x 110 mm, BNC connector, 1m cable (for pH 2700, PC 2700, Ion 2700)	29700.00
ECFC7252101B	General purpose plastic-body single junction gel-filled pH combination electrode, 12x90mm, BNC connector, 1m cable length	6750.00
ECFG7350401B	General purpose glass-body single junction refillable pH combination electrode, annular ceramic reference junction with protective sensor guard, 12x110mm, BNC connector, 1m cable length & 10ml refilling electrolyte	9990.00
AN-786-1	General purpose glass-body refillable indigenous pH combination electrode, BNC connector, 1m cable length, Brand Antech	2340.00
AN-ST-770	Indian electrode stand, Brand Antech	2160.00
ECPHELSTDC	Electrode stand with swivel arm	11700.00
ECELSTDCNEW	Electrode stand with swivel arm (for pH Tutor)	8550.00
01 X 321801	Electrode stand with accuflex arm (for 700 and 2700 series)	P.O.R
EB1700PWR	Universal power adapter 100-240V 50/60Hz with twist-and-lock connector (1710, 1720, 1730)	P.O.R
60X030130	100 /240VAC SMPS power adapter with US/UK/EUR/Japan plug ,9V,6W, centre +ve (for Cyber scan Tutor, 11 / 110 /510/ 700/1100 / 2100 series)	4950.00
60X426401	100 /240VAC SMPS power adapter , 9V,6W (150, 450 and 2700 series)	9000.00
ECFC72522R01B	General purpose plastic-body double junction refillable pH combination electrode, 12x90mm, BNC connector, 1m cable	14400.00

	length & 10ml refilling electrolyte	
ECFC7352901B	General purpose plastic-body "3-in-1" pH/Temp. combination electrode, 12x90mm, BNC connector, 1m cable length (for pH 5/6, Ion 6, pH 11/110, pH 510 & pH 1100/2100)	11700.00
ECFC7960201B	General purpose plastic-body double junction gel-filled ORP Electrode, 12x90mm, BNC connector, 1m cable length	P.O.R
AN-270	Dot matrix printer, Brand Antech	36000.00

Specialty pH Electrodes

ECFG7350401B	General purpose glass-body single junction refillable pH combination electrode, annular ceramic reference junction with protective sensor guard, 12x110mm, BNC connector, 1m cable length & 10ml refilling electrolyte	9990.00
ECFG7451901B	Glass-body pH combination electrode, reference Ag/AgCl sealed , 12x110mm, BNC connector, 1m cable length .Ideal for high temp. measurements and photographic samples	P.O.R
ECFG6350601B	Glass-body pH combination electrode, reference Ag/AgCl refillable , 8x55mm, BNC connector, 1m cable length .Ideal for high viscosity solutions such as emulsions, suspensions, paints and varnishes where frequent cleaning of the reference is necessary, aqueous pH measurements. Quality control, general laboratory and aquarium water	P.O.R
ECFG6351101B	Glass-body pH combination electrode, reference Ag/AgCl sealed , 8x55mm, BNC connector, 1m cable length .Ideal for Solid or semi-solid samples such as cheese, meats, fruits, bread, or other similar sample	P.O.R
ECFG7351101B	Glass-body pH combination electrode, reference Ag/AgCl refillable , 12x110 mm, BNC connector, 1m cable length .Ideal for high viscosity solutions such as emulsions, suspensions, paints and varnishes where frequent cleaning of the reference is necessary	P.O.R
ECFG4390401B	Glass-body pH combination micro-electrode, reference calomel refillable ,4x55 mm, BNC connector, 1m cable length .Ideal for micro sample, such as semi-micro cuvettes and NMR tube, research measurements, fruit juices, beer, milk and yogurt, tris buffers, clinical, and biological media containing proteins, creams, fats and cosmetics	P.O.R
ECFG7252001B	General purpose, flat-surface, glass-body single junction refillable pH combination electrode, 12x110mm, BNC connector, 1m cable length. Used for surface measurements such as paper, skin, textile, leather, agar	P.O.R
EC620185	Glass-body pH combination electrode, reference double junction ,Ag/AgCl Refillable , 10x102 mm, BNC connector, 1m cable length .Ideal for tris buffers, clinical, and biological media containing proteins, creams, fats, rugged use; ruggedized electrode tip, Aqueous media, Reference contamination problems which require a double junction reference, such as media containing sulfides, bromides, iodides, and cyanides	P.O.R
EC620130	Glass body, refillable, open pore ,reference double junction ,Ag/AgCl refillable,12x160 mm, BNC connector, 1m cable length(10ml electrolyte 620-430 included).Ideal for tris buffers, clinical, and biological media containing proteins, creams, fats, reference contamination problems which require a double	P.O.R



	junction reference, such as media containing sulfides, bromides, iodides, and cyanides , Aqueous media in general, low ionic strength solutions, such as high purity water	
EC620131	Glass-body pH combination electrode, reference double junction ,Ag/AgCl Sealed , 12x120 mm, BNC connector, 1m cable length .Ideal for tris buffers, clinical, and biological media containing proteins, creams, fats, reference contamination problems which require a double junction reference, such as media containing sulfides, bromides, iodides, and cyanides , aqueous media in general, high viscosity solutions such as emulsions, suspensions, paints and varnishes where frequent cleaning of the reference is necessary	22500.00
EC620132	Plastic-body pH combination electrode, reference double junction ,Ag/AgCl Sealed , 12x105 mm, BNC connector, 1m cable length .Ideal for tris buffers, clinical, and biological media containing proteins, creams, fats, reference contamination problems which require a double junction reference, such as media containing sulfides, bromides, iodides, and cyanides , aqueous media in general, low ionic strength solutions, such as high purity water	21600.00
EC620133	Glass body pH combination, polymer, spear tip, double pore electrode, reference double junction ,Ag/AgCl sealed , 6 x 80 mm, BNC connector, 1m cable length .Ideal for solid or semi-solid samples such as cheese, meats, fruits, bread, or other similar sample ,tris buffers, clinical, and biological media containing proteins, creams, fats, reference contamination problems which require a double junction reference, such as media containing sulfides, bromides, iodides, and cyanides , aqueous media in general	P.O.R
ECFC7252101B	General purpose plastic-body single junction gel-filled pH combination electrode, 12x90mm, BNC connector, 1m cable length	6750.00
ECFC7252201B	General purpose plastic-body double junction gel-filled pH combination electrode, 12X90mm, BNC connector, 1m cable length	9900.00
ECFC72521R01B	General purpose plastic-body single junction refillable pH combination electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	11700.00
ECFC72522R01B	General purpose plastic-body double junction refillable pH combination electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	14400.00
"3-in-1" pH/Temp Electrodes		
ECFC7352901B	General purpose plastic-body "3-in-1" pH/Temp. combination electrode, 12x90mm, BNC connector, 1m cable length (for pH 5/6, Ion 6, pH 11/110, pH 510 & pH 1100/2100)	11700.00
ECFC7352901W	General purpose plastic-body gel-filled "3-in-1" pH/Temp. combination electrode, 12x90mm, BNC and 6 pin connector, 1m cable length (for pH 310, 300, PC300 & PC510)	15300.00
ORP Electrodes		
ECFG7960101B	General purpose glass-body single junction refillable ORP electrode, 12x110mm, BNC connector, 1m cable length	P.O.R
ECFC7960101B	General purpose plastic-body single junction gel-filled ORP electrode, 12x90mm, BNC connector, 1m cable length	P.O.R
ECFC7960201B	General purpose plastic-body double junction gel-filled ORP Electrode, 12x90mm, BNC connector, 1m cable length	P.O.R

Ion Selective Electrodes		
Ammonia (NH ₃) Ion Electrode	Ammonia gas sensor	P.O.R
Ammonium (NH ₄ ⁺) Ion Electrode	Ammonium combination	P.O.R
Bromide (Br ⁻) Ion Electrode	Bromide combination	P.O.R
Cadmium (Cd ⁺²) Ion Electrode	Cadmium combination	P.O.R
Calcium (Ca ⁺²) Ion Electrode	Calcium combination	P.O.R
Carbon Dioxide (CO ₂) Ion Electrode	Carbon-dioxide gas sensor	P.O.R
Chloride (Cl ⁻) Ion Electrode	Chloride combination	P.O.R
Copper (Cu ⁺²) Ion Electrode	Copper combination	P.O.R
Cyanide (CN ⁻) Ion Electrode	Cyanide combination	P.O.R
Fluoride (F ⁻) Ion Electrode	Fluoride combination	P.O.R
Fluoroborate (BF ₄ ⁻) Ion Electrode	Fluoroborate combination	P.O.R
Iodide (I ⁻) Ion Electrode	Iodide Combination	P.O.R
Lead (Pb ⁺²) Ion Electrode	Lead combination	P.O.R
Nitrate (NO ₃ ⁻) Ion Electrode	Nitrate combination	P.O.R
Perchlorate (ClO ₄ ⁻) Ion Electrode	Perchlorate combination	P.O.R
Potassium (K ⁺) Ion Electrode	Potassium combination	P.O.R
Silver (Ag ⁺) Ion Electrode	Silver combination	P.O.R
Sodium (Na ⁺) Ion Electrode	Sodium combination	P.O.R
Sulfide (S ⁻²) Ion Electrode	Sulfide combination	P.O.R
Surfactant (X ⁺ /X ⁻) Ion Electrode	Surfactant combination	P.O.R
Water Hardness (Ca ⁺² /Mg ⁺²) Ion Electrode	Water hardness combination	P.O.R
Note: All ISEs come with 1-meter cable length and BNC type connector		

Calibration Standards And ISA For Ion Selective Electrodes (Indigenous, Brand Antech)

Ammonia Ion Electrode Solutions

AM-CAL1S	Standard 0.1M (500 ml)	6300.00
AM-CAL2S	Standard 1000 ppm (500 ml)	6300.00
AM-CAL3S	Standard 100 ppm (500 ml)	6930.00
AM-ISA1S	Ionic strength adjuster (500 ml)	6930.00

Ammonium Ion Electrode Solutions		
AMM-CAL1S	Standard 0.1M (500 ml)	6300.00
AMM-CAL2S	Standard 1000 ppm (500 ml)	6300.00
AMM-CAL3S	Standard 100 ppm (500 ml)	6930.00
AMM-ISA1S	Ionic strength adjuster (500 ml)	6930.00
Bromide Ion Electrode Solutions		
BR-CAL1S	Standard 0.1M (500 ml)	6300.00
BR-CAL2S	Standard 1000 ppm (500 ml)	6300.00
BR-ISA1S	Ionic strength adjuster (500 ml)	6930.00
Cadmium Ion Electrode Solutions		
CD-CAL1S	Standard 0.1M (500 ml)	6300.00
CD-CAL2S	Standard 1000 ppm (500 ml)	6300.00
CD-ISA1S	Ionic strength adjuster (500 ml)	6930.00
Calcium Ion Electrode Solutions		
CA-CAL1S	Standard 0.1M (500 ml)	6300.00
CA-CAL2S	Standard 1000 ppm (500 ml)	6300.00
CA-CAL3S	Standard 100 ppm (500 ml)	6930.00
CA-ISA1S	Ionic strength adjuster(500 ml)	6930.00
Carbon Dioxide Ion Electrode Solutions		
CO-CAL1S	Standard 0.1M (500 ml)	6300.00
CO-CAL2S	Standard 1000 ppm (500 ml)	6300.00
CO-CAL3S	Standard 100 ppm(500 ml)	6930.00
CO-ISA1S	Ionic strength adjuster (500 ml)	6930.00
Chloride Ion Electrode Solutions		
CL-CAL1S	Standard 0.1M (500 ml)	6300.00
CL-CAL2S	Standard 1000 ppm (500 ml)	6300.00
CL-CAL3S	Standard 100 ppm (500 ml)	6930.00
CL-ISA1S	Ionic strength adjuster (500 ml)	6930.00
Copper Ion Electrode Solutions		
CU-CAL1S	Standard 0.1M (500 ml)	6300.00
CU-CAL2S	Standard 1000 ppm (500 ml)	6300.00
CU-ISA1S	Ionic strength adjuster (500 ml)	6930.00
Fluoride Ion Electrode Solutions		
FL-CAL1S	Standard 0.1M (500 ml)	6300.00
FL-CAL2S	Standard 1000 ppm (500 ml)	6300.00
FL-CAL3S	Standard 100 ppm (500 ml)	6930.00
FL-ISA1S	Ionic strength adjuster (500 ml)	6930.00
FL-ISA2S	Ionic strength adjuster (500 ml) (low concentration)	6930.00
Fluoroborate Ion Electrode Solutions		

FB-CAL2S	Standard 1000 ppm (500 ml)	10800.00
FB-CAL3S	Standard 100 ppm (500 ml)	10800.00
FB-ISA1S	Ionic strength adjuster (500 ml)	12600.00
Lead Ion Electrode Solutions		
PB-CAL1S	Standard 0.1M (500 ml)	12600.00
PB-CAL2S	Standard 1000 ppm (500 ml)	10800.00
PB-ISA1S	Ionic strength adjuster (500 ml)	12600.00
Nitrate Ion Electrode Solutions		
NT-CAL1S	Standard 0.1M (500 ml)	6750.00
NT-CAL2S	Standard 1000 ppm (500 ml)	6750.00
NT-CAL3S	Standard 100 ppm (500 ml)	6930.00
NT-ISA1S	Ionic strength adjuster (500 ml)	6930.00
Perchlorate Ion Electrode Solutions		
PC-CAL2S	Standard 1000 ppm (500 ml)	10800.00
PC-ISA1S	Ionic strength adjuster (500 ml)	12600.00
Potassium Ion Electrode Solutions		
KO-CAL1S	Standard 0.1M (500 ml)	6300.00
KO-CAL2S	Standard 1000 ppm (500 ml)	6930.00
KO-ISA1S	Ionic strength adjuster (500 ml)	6930.00
Silver / Sulfide Ion Electrode Solutions		
SS-CAL1S	Standard 0.1M (500 ml)	12600.00
SS-CAL2S	Standard 1000 ppm (500 ml)	10800.00
SS-ISA1S	Ionic strength adjuster (500 ml)	10800.00
Surfactant Ion Electrode Solutions		
SF-CAL2S	Standard 1000 ppm (500 ml)	10800.00
SF-ISA1S	Ionic strength adjuster (500 ml)	12600.00
Sodium Ion Electrode Solutions		
NA-CAL1S	Standard 0.1M (500 ml)	6750.00
NA-CAL2S	Standard 1000 ppm (500 ml)	6750.00
NA-CAL3S	Standard 100 ppm (500 ml)	6930.00
NA-ISA1S	Ionic strength adjuster (500 ml)	6930.00
Iodide Ion Electrode Solutions		
IO-CAL1S	Standard 0.1M (500 ml)	6750.00
IO-CAL2S	Standard 1000 ppm (500 ml)	6750.00
IO-CAL3S	Standard 100 ppm (500 ml)	6930.00
IO-ISA1S	Ionic strength adjuster (500 ml)	6930.00
Water Hardness Ion Electrode Solutions		

WH-CAL2S	Standard 1000 ppm (500 ml)	12600.00
WH-CAL3S	Standard 100 ppm (500 ml)	12600.00
WH-ISA1S	Ionic strength adjuster (500 ml)	12600.00

Note: Calibration standards of specific strength can be provided on request



Waterproof Conductivity / TDS / Salinity Pocket Testers		
ECOECTESTLOW	Waterproof EcoTestr EC low tester with ATC, 1 point calibration	6930.00
ECOECTESTHIGH	Waterproof EcoTestr EC High Tester with ATC; 1 point calibration	6930.00
ECTEST11	Waterproof ECTestr11 dual range tester with ATC & temperature display (0 - 2000 μ S/cm; 0 -20.00 mS/cm)	10890.00
ECTEST11PLS	Waterproof ECTestr11+ multi range tester with ATC & temperature display (0 - 200.0 μ S/cm; 0 - 2000 μ S/cm; 0 - 20.00 mS/cm)	17100.00
ECOTDSTESTLOW	Waterproof EcoTestr TDS low tester with ATC, 1 point calibration	6930.00
ECOTDSTESTHIGH	Waterproof EcoTestr TDS high tester with ATC; 1 point calibration	6930.00
TDSTEST11	Waterproof TDSTestr11 dual range tester with ATC & temperature display (0 - 1000 ppm; 0 -10.00 ppt)	10890.00
TDSTEST11PLS	Waterproof TDSTestr11+ multi range tester with ATC & temperature display (0 - 100.0 ppm; 0 -1000 ppm; 0 - 10.00 ppt)	17100.00
SALTTEST11	Waterproof SaltTestr11 tester with ATC & temperature display (0 - 10.00 ppt)	17100.00



Accessories		
ECTDSENSORPLUS	Replacement sensor for ECTestr10+,TDSTestr10+ series & ECTestr11+, TDSTestr11+ , cup type	4680.00
ECTDSENSOR	Replacement sensor for ECTestr, ECTestr10, TDSTestr, TDSTestr10 series, ECTestr11, TDSTestr11 & all SaltTestr series, 2-pin type	4680.00

Economy Conductivity / TDS / Salinity Handheld Meters		
ECCON603PLUSK	COND 6+ conductivity meter with electrode CONSEN91B & conductivity carrying kit set	P.O.R
ECTDS603PLUSK	TDS 6+ TDS meter with electrode CONSEN91B & TDS carrying kit set	P.O.R
ECSALT603PLUSK	Salt 6+ salinity meter with electrode CONSEN91B & salinity carrying kit set	P.O.R

Waterproof Conductivity / TDS / Salinity Handheld Meters

ECCONWP15003K	CON 150-meter kit: meter, conductivity cell CONSEN91W (K = 1.0), grip-clip, two AA batteries, hard carry case, calibration solutions	P.O.R
ECCONWP45003K	CON 450-meter kit: meter, conductivity cell, CONSEN91W (K = 1.0), grip-clip, two AA batteries, hard carry case, USB cable, calibration solutions	P.O.R



Waterproof Conductivity / TDS / Salinity /Resistivity Handheld Meters

ECCONWP61043K	Waterproof CyberScan CON 610 Conductivity/TDS/ Resistivity/Salinity meter with 3m cable 4-cell electrode CONSEN9203J K=0.530, DAS software, power adapter & Conductivity/TDS carrying kit set	P.O.R
ECCONWP60043K	Waterproof CyberScan CON 600 Conductivity/TDS meter with 3m cable 4-cell electrode CONSEN9203J K=0.530, DAS software, power adapter & conductivity/TDS carrying kit set	P.O.R

Accessories

CONSEN91B	2 stainless steel rings ultem-body electrode with ATC, cell constant K=1.0, 16x144 mm, BNC connector, 1m cable length (for CON 6+, TDS 6+, SALT 6+)	27000.00
CONSEN91W	2 stainless steel rings ultem-body electrode with ATC, cell constant K=1.0, 16x144 mm, 6-pin connector, 1m cable length (for CON 110 , CON 11, CON 410 , CON 400, PC 300, CON 510 & PC 510 ,CON 150, CON 450, PC 450)	27000.00
CONSEN9203J	4 cell bulls-eye epoxy-body electrode with ATC, K=0.530 12x120 mm, 8-pin connector, 3m cable length (for COND600, COND610, PC650, PCD650)	P.O.R
01X030132	Universal SMPS,100 /240VAC,9V,6W, centre +ve power adapter with US/UK/EUR/Japan plug (for Cyberscan 600 series)	13500.00
60X030130	100 /240VAC SMPS power adapter with US/UK/EUR/Japan plug ,9V,6W, centre +ve (for Cyberscan 11 / 110 / 1100 / 2100 series)	4950.00
60X426401	100 /240VAC SMPS power adapter, 9V,6W (150, 450 and 2700 series)	9000.00
CONSEN72W	2 stainless steel rings glass- body electrode with ATC, cell constant K=0.1, 16x110 mm, 6-pin connector, 1m cable length (for CON 110 , CON 11, CON 410 , CON 400, PC 300, CON 510))	P.O.R
CONSEN92W	2-cell conductivity/ATC electrode, 10.0 cell constant, platinum sensor, epoxy-body (150 / 450 series)	27000.00
CONSEN73W	2 platinum rings epoxy-body electrode with ATC, cell constant K=10.0, 16x110 mm, 6-pin connector, 1m cable length (for CON 110 , CON 11, CON 410 , CON 400, CON 510)	P.O.R
CONSEN9103J	2 stainless steel rings ultem-body electrode with ATC, cell constant K=1.0, 16x144 mm, 8-pin connector, 3m cable length (for COND600, COND610, PC650, PCD650)	P.O.R
ECCONSEN93J	2 cell electrode with ATC, cell constant K=0.1 , 16x110 mm, 8-pin connector, 1m cable length (for CON600, COND610, PC650, PCD650)	P.O.R



Conductivity / TDS / Salinity /Resistivity Bench Meters

EBEC172001	1720 meter with CONSEN9501D 2-cell K = 1.0 ultem -body conductivity/ATC electrode, electrode stand, PC cable, and universal power adapter	P.O.R
------------	-------------------------------------------------------------------------------------------------------------------------------------------	-------



ECCON70043S	CON 700 meter with conductivity/ATC probe CONSEN9501D ,K=1.0 , integral electrode holder & 100/240 VAC adapter	P.O.R
ECCON270043S	CON 2700 meter with 4-cell conductivity probe CONSEN9201D K=0.530, integral electrode holder & 100/240 VAC adapter, RS232 cable	P.O.R

Accessories

CONSEN91W	2 stainless steel rings ultem-body electrode with ATC, cell constant K=1.0, 16x144 mm, 6-pin connector, 1m cable length (for CON 110 , CON 11, CON 410 , CON 400, PC 300, CON 510 & PC 510 ,CON 150, CON 450, PC 450)	27000.00
CONSEN72W	2 stainless steel rings glass- body electrode with ATC, cell constant K=0.1, 16x110 mm, 6-pin connector, 1m cable length (for CON 110 , CON 11, CON 410 , CON 400, PC 300, CON 510)	P.O.R
CONSEN73W	2 platinum plates epoxy-body electrode with ATC, cell constant K=10.0, 16x110 mm, 6-pin connector, 1m cable length (for CON 110 , CON 11, CON 410 , CON 400, PC 300, CON 510)	P.O.R
93X546101	2-cell conductivity/ATC electrode, 0.1 cell constant, SS sensor, epoxy-body (700,2700,1720)	34200.00
CONSEN9201D	4-cell conductivity/ATC electrode K=0.530, graphite sensor, epoxy-body (2700,1720)	P.O.R
CONSEN9501D	2-cell conductivity/ATC electrode K=1.0, stainless steel sensor, ultem-body (700,2700,1720)	27000.00

Economy Dissolved Oxygen Handheld Meter

ECDO602PLUSK	Galvanic dissolved oxygen meter with ECDO6HANDY3M ,3m cable electrode, 2 assembled membrane cap housing, 1 refilling electrolyte (10ml) & carrying kit set	P.O.R
--------------	------------------------------------------------------------------------------------------------------------------------------------------------------------	-------



Waterproof Dissolved Oxygen Handheld Meters : RDO technology

ECDOWP45003K	DO 450-meter Kit, RDO electrode with sensor cap RDO3M, two AA batteries, hard carry case, USB cable, RDO stainless steel weight/guard, RDO calibration chamber	P.O.R
--------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------	-------



Waterproof Dissolved Oxygen Handheld Meters

ECDOWP60041K	Waterproof CyberScan DO 600 dissolved oxygen meter with 10 ft cable electrode ECDOHANDYNEW, DAS software, power adapter & carrying kit set	P.O.R
--------------	--------------------------------------------------------------------------------------------------------------------------------------------	-------



Accessories

ECDO6HANDY3M	Galvanic dissolved oxygen electrode with ATC, 3m cable length (for DO 6)	P.O.R
ECDO6HANDY	Galvanic dissolved oxygen electrode with ATC, 1 m cable (DO 6+, DO 700, 1730)	P.O.R
ECDOHANDYNEW	Galvanic dissolved oxygen electrode with ATC, 3 m cable length , 1 assembled membrane cap housing, 1 refilling electrolyte (60ml) and 1 scouring pad (for DO110, DO 300, PD 300, DO600, PD650, CD650, PCD650)	P.O.R

Accessories		
01X211226	DO refilling electrolyte (60 ml) (for DO 6, DO100, DO110, DO 300, PD 300, DO 600, CD 650, PD 650 & PCD 650)	9000.00
01X241608	Assembled membrane cap housing for ECDO6HANDY & ECDO6HANDY3M (1 unit) (for DO 6)	10800.00
01X623901	Assembled membrane cap housing (for DO100, DO110, DO 300 & PD 300)	18000.00
01X241603	Membranes & O-rings (pack of 5 units) (for DO100, DO110, DO 300 & PD 300)	18000.00
15X241502	Tool for ECDOHANDYNEW membrane housing	18000.00
ECDOZEROSOLN	Zero oxygen solution, 0 % DO, 480 ml	9000.00
60X030130	100 /240VAC SMPS power adapter with US/UK/EUR/Japan plug ,9V,6W, centre +ve (for Cyberscan 11 / 110 / 1100 / 2100 series)	4950.00
01X030132	Universal SMPS,100 /240VAC,9V,6W, centre +ve power adapter with US/UK/EUR/Japan plug (for Cyberscan 600 series)	13500.00
60X426401	100 /240VAC SMPS power adapter , 9V,6W (150, 450 and 2700 series)	9000.00
EB1700PWR	Universal power adapter 100-240V 50/60Hz with twist-and-lock connector (1710, 1720, 1730)	P.O.R
RDOCAP	Replacement RDO cap	P.O.R
RDO3M	RDO Probe 3 M / 10 ft	P.O.R
RDO6M	RDO Probe 6 M / 20 ft	P.O.R
RDO15M	RDO Probe 15 M / 50 ft	P.O.R
RDOCALCHAMBER	RDO Calibration Chamber	P.O.R
RDOWEIGHT	RDO Weight	P.O.R

Dissolved Oxygen Bench Meters

EBDX173001	1730 DO meter with DO6HANDY galvanic DO/ATC probe 1 m cable, electrode stand, PC cable, and universal power adapter	P.O.R
ECDO70042S	DO 700 meter with DO6HANDY galvanic DO/ATC probe 1 m cable, integral electrode holder & 100/240 VAC adapter	P.O.R
ECDO270042	DO 2700 meter with self-stirring dissolved oxygen / BOD electrode (EC620SSP), RS232C cable & 100/240 VAC adapter, RS232 cable	P.O.R

Accessories

EC620SSP	DO/BOD electrode with self-stirring mechanism, 1m cable length	P.O.R
ECDOZEROSOLN	Zero oxygen solution, 0 % DO, 480 ml	9000.00

Waterproof Multi-Parameter Pocket Testers



EXPERTCTS	Waterproof expert CTS Conductivity/TDS/Salinity pocket tester with ATC and temperature display (0.00-20.00mS/cm; 0.00 -20.00 ppt; 0.0 -10.0 ppt)	9900.00
PCTEST35	Waterproof PCTestr 35 pH/Conductivity/Temp tester with ATC; (± 0.1 pH resolution; 0 - 2000 μ S/cm; 0 - 20.00 mS/cm)	18900.00
PTTEST35	Waterproof PTTestr 35 pH/TDS/Temp tester with ATC; (± 0.1 pH resolution; 0 - 1000 ppm; 0 - 10.00 ppt)	18900.00
PCSTEST35	Waterproof PCSTestr 35 pH/Conductivity/TDS/Salinity/Temp tester with ATC; (± 0.01 pH resolution; 0 - 200.0 μ S/cm; 0 - 2000 μ S/cm; 0 - 20.00 mS/cm; 0 - 100.0 ppm; 0 - 1000 ppm; 0 - 10.00 ppt; 0 - 100.0 ppm; 0 - 1000 ppm; 0 - 10.00 ppt; 0 - 1.00%)	24300.00
PCSTEST35K	Waterproof PCSTestr 35 pH/Conductivity/TDS/Salinity/Temp tester carrying kit with 1 x pH 4.01 , pH 7.00, 1413 μ S standard solutions and 1 x deionized rinse water (60 mL each)	28800.00

Accessories

PCSENSOR	Replacement pH/Conductivity/Temp sensor for PCTestr 35, PTTestr 35, PCSTestr 35	9450.00
----------	---------------------------------------------------------------------------------	---------

Waterproof Multi-Parameter Handheld Meters Handheld Meters

ECPCWP45004K	PC 450 meter with separate pH and conductivity probes kit with double junction pH electrode ECFC7252201B, conductivity cell CONSEN91W (K = 1.0) , grip-clip, two AA batteries, hard carry case, USB cable and calibration solutions	P.O.R
ECPDWP45004K	PD 450-meter kit: meter, pH electrode ECDA9350603B, RDO electrode with sensor cap RDO3M, two AA batteries, hard carry case, USB cable, RDO stainless steel weight/guard, RDO calibration chamber, calibration solutions	P.O.R

Waterproof Multi-Parameter Handheld Meters

ECPCWP65043K	Waterproof CyberScan PC 650 pH/ mV/ Ion/ Conductivity/ TDS/ resistivity/ salinity meter with double junction pH electrode ECFC7252203B, 4-cell conductivity probe CONSEN9203J, DAS software, multi-probe holder, power adapter & carrying kit set (all Probes comes with 3m long cable).	P.O.R
--------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------

Note: PC 650 pH/Conductivity carrying kit consists of a carrying case with 1 x pH 4.01, pH 7.00 buffer solutions, 1 x 12.88 mS KCl standard solution and 1 x deionised (rinse) water (60 ml each)

ECCDWP65043K	Waterproof CyberScan CD 650 Conductivity/ TDS/ Resistivity/ Salinity/ Dissolved Oxygen meter with 4-cell conductivity probe CONSEN9203J, dissolved oxygen probe ECDOHANDYNEW, DAS software, multi-probe holder, power adapter & carrying kit set (all Probes comes with 3m long cable)	P.O.R
--------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------

Note: CD 650 Conductivity/DO carrying kit consists of a carrying case with 1 x 1413 uS, 12.88 mS KCl, 3000 ppm standard solutions and 1 x deionised (rinse) water (60 ml each)

ECPDWP65043K	Waterproof CyberScan PD 650 pH/ mV/ Ion/ Dissolved Oxygen meter with double junction pH electrode ECFC7252203B, ATC Probe ECPHWPTM03J, dissolved oxygen probe ECDOHANDYNEW, DAS software, multi-Probe holder, power adapter & carrying kit set (all probes comes with 3m long cable).	P.O.R
--------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------

Note: PD 650 pH/DO carrying kit consists of a carrying case with 1 x pH 4.01, pH 7.00 buffer solutions, 1 x Storage solution and 1 x deionised (rinse) water (60 ml each)

ECPCDWP65044K	Waterproof CyberScan PCD 650 pH/ mV/ Ion/ Conductivity/ TDS/ Resistivity/ Salinity/ Dissolved Oxygen meter with double junction pH electrode ECFC7252203B, 4-cell conductivity probe	P.O.R
---------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------



	CONSEN9203J, dissolved oxygen probe ECDOHANDYNEW, DAS software, multi-probe holder, power adapter & carrying kit set (all Probes comes with 3m long cable).	
--	-------------------------------------------------------------------------------------------------------------------------------------------------------------	--

Note: PCD 650 pH/Conductivity/DO carrying kit consists of a carrying case with 1 x pH 4.01, pH 7.00 buffer solutions, 1 x 12.88 mS KCl standard solution and 1 x deionised (rinse) water (60 ml each)

Accessories		
ECFC7252201B	General purpose plastic-body double junction gel-filled pH combination electrode, 12X90mm, BNC connector, 1m cable length	9900.00
CONSEN91W	2 stainless steel rings ultem-body electrode with ATC, cell constant K=1.0, 16x144 mm, 6-pin connector, 1m cable length (for CON 110 , CON 11, CON 410 , CON 400, PC 300, CON 510 & PC 510 ,CON 150, CON 450, PC 450)	27000.00
CONSEN92W	2-cell conductivity/ATC electrode, 10.0 cell constant, platinum sensor, epoxy-body (150 / 450 series)	27000.00
ECDOHANDYNEW	Galvanic dissolved oxygen electrode with ATC, 3 m cable length , 1 assembled membrane cap housing, 1 refilling electrolyte (60ml) and 1 scouring pad (for DO110, DO 300, PD 300, DO600, PD650, CD650, PCD650)	P.O.R
ECPHWPTM03J	ATC probe (for pH 620, 610, 600, PC650, PD650, PCD650 only); 3m cable length	12600.00
ECFC7252203B	General purpose plastic-body double junction gel-filled pH combination electrode, 12x90mm, BNC connector, 3m cable length	P.O.R
CONSEN9203J	4 cell bulls-eye epoxy-body electrode with ATC, 12x120 mm, 8-pin connector, 3m cable length (for COND600, COND610, PC650, PCD650)	P.O.R
60X426401	100 /240VAC SMPS power adapter , 9V,6W (150, 450 and 2700 series)	9000.00
01X623901	Assembled membrane cap housing (for DO100, DO110, DO 300 & PD 300)	18000.00
01X211226	DO refilling electrolyte (60 ml) (for DO 6, DO100, DO110, DO 300, PD 300, DO 600, CD 650, PD 650 & PCD 650)	9000.00
01X241603	Membranes & O-rings (pack of 5 units) (for DO100, DO110, DO 300 & PD 300)	18000.00
01X030132	Universal SMPS,100 /240VAC,9V,6W, centre +ve power adapter with US/UK/EUR/Japan plug (for Cyberscan 600 series)	13500.00
PHWPTM01W	ATC probe (for pH 310, pH 300, PC300 ,PC510, PH 150, CON 150, PH 450, CON 450, PC 450) 1m cable length	12600.00
ECPHWPTM01J	ATC probe (for pH 620, 610, 600, PC650, PD650, PCD650 only); 1m cable length	12600.00
ECFC72522R01B	General purpose plastic-body double junction refillable pH combination electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	14400.00
ECFC7352901W	General purpose plastic-body gel-filled "3-in-1" pH/Temp. Combination electrode, 12x90mm, BNC and 6 pin connector, 1m cable length (for pH 310, 300, PC300 & PC510)	15300.00
ECFC7352901J	General purpose plastic-body gel-filled "3-in-1" pH/Temp. combination electrode, 12x90mm, BNC and 8 pin connector, 1m cable length (for pH 620, 610, 600, PC650, PD650, PCD650 only)	15300.00
CONSEN9103J	2 stainless steel rings ultem-body electrode with ATC, cell constant K=1.0, 16x144 mm, 8-pin connector, 3m cable length (for COND600, COND610, PC650, PCD650)	P.O.R
ECCONSEN93J	2 cell electrode with ATC, cell constant K=0.1 , 16x110 mm, 8-	P.O.R

pin connector, 1m cable length (for CON600, COND610, PC650, PCD650)

Multi-Parameter Bench Meters

ECPC70043S	PC 700 meter with pH electrode (ECFC7252101B), conductivity/ATC probe (CONSEN9501D), integral electrode holder & 100/240 VAC adapter	P.O.R
ECPC270043S	PC 2700 meter with pH electrode (ECFG7370101B), 4-cell conductivity/ATC electrode, graphite sensor, epoxy-body(CONSEN9201D), integral electrode holder , RS232 cable & 100/240 VAC adapter	P.O.R

Accessories

EC620130	Glass body, refillable, open pore (10ml electrolyte 620-430 included)	P.O.R
ECFC7252201B	General purpose plastic-body double junction gel-filled pH combination electrode, 12x90mm, BNC connector, 1m cable length	9900.00
CONSEN91W	2 stainless steel rings ultem-body electrode with ATC, cell constant K=1.0, 16x144 mm, 6-pin connector, 1m cable length (for CON 110 , CON 11, CON 410 , CON 400, PC 300, CON 510 & PC 510 ,CON 150, CON 450, PC 450)	27000.00
PHWPTEM01W	ATC probe (for pH 310, pH 300, PC300 ,PC510, PH 150, CON 150, PH 450, CON 450, PC 450) 1m cable length	12600.00
ECFC7352901W	General purpose plastic-body gel-filled "3-in-1" pH/Temp. combination electrode, 12x90mm, BNC and 6 pin connector, 1m cable length (for pH 310, 300, PC300 & PC510)	15300.00
ECFC72522R01B	General purpose plastic-body double junction refillable pH combination electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	14400.00
ECFG7350401B	General purpose glass-body single junction refillable pH combination electrode, annular ceramic reference junction with protective sensor guard, 12x110mm, BNC connector, 1m cable length & 10ml refilling electrolyte	9990.00
ECFC7960201B	General purpose plastic-body double junction gel-filled ORP electrode, 12x90mm, BNC connector, 1m cable length	P.O.R
ECFC79602R01B	General purpose plastic-body double junction refillable ORP electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	P.O.R
CONSEN9201D	4-cell conductivity/ATC electrode K=0.530, graphite sensor, epoxy-body (2700,1720)	P.O.R
CONSEN9501D	2-cell conductivity/ATC electrode K=1.0, stainless steel sensor, ultem-body (700,2700,1720)	27000.00
93X546101	2-cell conductivity/ATC electrode, 0.1 cell constant, SS sensor, epoxy-body (700,2700,1720)	34200.00

Waterproof Turbidity Portable Meter

ECTN100IR	Waterproof TN-100 handheld turbidity meter with set of 4 calibration standards (800, 100, 20.0 & 0.02 NTU), sample vials, lint-free cloth, silicone oil, batteries, and hard carrying case	P.O.R
-----------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------

Accessories		
TN100CALKIT	Calibration kit set for TN100IR (0.02, 20.0, 100, 800 NTU) , 4 x 60 ml	P.O.R
ECTN100CUVKIT	Pack of 3 sample cuvettes (TN100IR)	9900.00
ECSILICONEOIL	Silicone oil (10 ml) for TN100IR	3150.00
01X344318	10.0 NTU calibration standard (125 mL)	P.O.R

Thermo Scientific Temperature Hand-Held Meters

Thermo Scientific Temp 300 Series Dual-Input Thermocouple Data logging Thermometers

TSTEMP300	Thermo Scientific Temp 300 dual-input thermocouple data logger with rubber armour/stand (Probe Not Included)	P.O.R
-----------	--------------------------------------------------------------------------------------------------------------	-------

Thermo Scientific Temp 10 Series Single-Input J , K, T Type Thermocouple Thermometer

TSTEMP10J	Thermo Scientific Temp 10 Type J thermocouple thermometer with rubber armour/stand (probe not included)	P.O.R
TSTEMP10K	Thermo Scientific Temp 10 Type K thermocouple thermometer with rubber armour/stand (probe not included)	P.O.R
TSTEMP10T	Thermo Scientific Temp 10 Type T thermocouple thermometer with rubber armour/stand (probe not included)	P.O.R



Thermo Scientific Temp 360 Precision RTD Data logging Thermometer

TSTEMP360	Thermo Scientific RTD Data logger with rubber armour/stand (probe not included)	P.O.R
-----------	---------------------------------------------------------------------------------	-------

Thermo Scientific Temp16 Single-Input Precision RTD Thermometer

TSTEMP16	Thermo Scientific thermistor thermometer with rubber armour / stand (probe not included)	P.O.R
----------	------------------------------------------------------------------------------------------	-------

Thermo Scientific Temp14 Single-Input Precision RTD Thermometer

TSTEMP14	Thermo Scientific Temp 14 thermistor thermometer (probe not included)	P.O.R
----------	-----------------------------------------------------------------------	-------

Accessories

60X030134	100/240 VAC,9V,6W,power adapter for 300 series	P.O.R
30X379302	USB cable for 300 series	P.O.R

Thermocouple Type J,K Or T Type Probes To Be Sourced Separately

RTD Pt 100 Probes To Be Sourced Separately

Specialty Meters

ECPHSIMULATOR	Precision hi-low impedance & multiple buffers pH simulator (with BNC-BNC cable provided)	P.O.R
---------------	------------------------------------------------------------------------------------------	-------

pH/ORP Calibration Standards		
pH Buffer Solutions (480 ml Per Bottle)		
ECBU1BT	pH 1.68 buffer solution, 480 ml	2196.00
ECBU4BTC	pH 4.01 buffer solution (colored) , 480 ml	2196.00
ECBU4BT	pH 4.01 buffer solution (colorless) , 480 ml	2196.00
ECBU686BT	pH 6.86 buffer solution, 480 ml	2196.00
ECBU7BTC	pH 7.00 buffer solution (colored) , 480 ml	2196.00
ECBU7BT	pH 7.00 buffer solution (colorless) , 480 ml	2196.00
ECBU9BT	pH 9.00 buffer solution, 480 ml	2196.00
ECBU918BT	pH 9.18 buffer solution, 480 ml	2196.00
ECBU10BTC	pH 10.01 buffer solution (colored) , 480 ml	2196.00
ECBU10BT	pH 10.01 buffer solution (colorless) , 480 ml	2196.00
ECBU12BT	pH 12.45 buffer solution, 480 ml	2196.00
pH Buffer solutions (1 ltr Per Bottle)		
ECBU4BTC1LIT	pH 4.01 buffer solution (red) , 1000 ml	3780.00
ECBU7BTC1LIT	pH 7.00 buffer solution (yellow) , 1000 ml	3780.00
ECBU10BTC1LIT	pH 10.01 buffer solution (blue) , 1000 ml	3780.00
pH Buffer Sachets (20 x 20 ml Per Box)		
ECBU4BS	pH 4.01 buffer sachets (NIST traceable ,20 x 20 ml per box)	11700.00
ECBU7BS	pH 7.00 buffer sachets (NIST traceable ,20 x 20 ml per box)	11700.00
ECBU10BS	pH 10.01 buffer sachets (NIST traceable ,20 x 20 ml per box)	11700.00
ECRINWT	pH deionized water rinse sachets (NIST traceable ,20 x 20 ml per box)	10800.00
ORP Solutions (480 ml Per Bottle)		
ECORPPRE	Pre-treatment solution (475 mV) , 480 ml	4500.00
ECORPQUIN	Quinhydrone 263 (263 mV, $\pm 15\text{mV}$ to $\pm 30\text{mV}$ @ 25°C) , 480 ml	4500.00
ECORPQUIN086	Quinhydrone 86 (86 mV) , 480 ml	4500.00
Other Solutions (480 ml Per Bottle)		
ECRE001	Saturated potassium chloride with silver chloride for single junction pH electrodes, 480 ml	16200.00
ECRE002	Saturated potassium chloride for double junction pH electrodes, 480 ml	17100.00
ECRE005	Storage solution for pH electrodes, 480 ml	8100.00
ECDPCBT	Protein cleaning solution for pH electrode, 480 ml	8100.00
Conductivity/TDS Calibration Standards		
Conductivity Standard Solutions (480 ml Per Bottle)		
ECCON84BT	84 $\mu\text{S/cm}$ KCl calibration solution, 480 ml	2430.00
ECCON100BT	100 $\mu\text{S/cm}$ KCl calibration solution, 480 ml	2430.00
ECCON500BT	500 $\mu\text{S/cm}$ KCl calibration solution, 480 ml	2430.00
ECCON1413BT	1413 $\mu\text{S/cm}$ KCl calibration solution, 480 ml	2430.00

ECCON2764BT	2764 μ S/cm KCl calibration solution, 480 ml	2430.00
ECCON1288BT	12.88 mS/cm KCl calibration solution, 480 ml	2430.00
ECCON1118BT	111.8 mS/cm KCl calibration solution, 480 ml	2430.00
ECCON5000BT	5.0 mS/cm KCl calibration solution, 480 ml	2430.00
Conductivity/Salinity Sachets (20 x 20 ml Per Box)		
ECCON10BS	10 μ S/cm KCl conductivity sachets (NIST traceable ,20 x 20 ml per box)	11700.00
ECCON447BS	447 μ S/cm KCl conductivity sachets (NIST traceable ,20 x 20 ml per box)	11700.00
ECCON1413BS	1413 μ S/cm KCl conductivity sachets (NIST traceable ,20 x 20 ml per box)	11700.00
ECCON2764BS	2764 μ S/cm KCl conductivity sachets (NIST traceable ,20 x 20 ml Per Box)	11700.00
ECCON15000BS	15000 uS/cm KCl conductivity sachets (NIST traceable ,20 x 20 ml per box)	11700.00
ECCON3000BS	3000 ppm KCL salinity calibration sachets (NIST traceable ,20 x 20 ml per box)	11700.00
TDS 442 Standard Solutions (480 ml Per Bottle)		
EC44250BT	50 ppm 442 calibration solution, 480 ml	2430.00
EC442300BT	300 ppm 442 calibration solution, 480 ml	2430.00
EC4421000BT	1000 ppm 442 calibration solution, 480 ml	2430.00
EC4423000BT	3000 ppm 442 calibration solution, 480 ml	2430.00
ECNACL5PPT	5 ppt Nacl calibration solution, 480 ml	2880.00
ECNACL25PPT	25 ppt Nacl calibration solution, 480 ml	2880.00
ECNACL45PPT	45 ppt Nacl calibration solution, 480 ml	2880.00



**For Online / Process Instrument Requirement Please Contact
AquaSensors – Analytical Water Quality & Process
Measurement Systems**

Thermo Scientific AquaSensors offers innovative online analytical measurement systems for water quality and process monitoring and control applications. Measurements include pH, ORP, Contacting and Toroidal Conductivity, Resistivity, Dissolved Oxygen (ppm & trace ppb), , RDO, Dissolved Ozone, drinking water & wide-range Turbidity, Suspended Solids and Free Chlorine. The patented DataStick measurement system features pre-calibrated plug-in sensor heads that provide 24-bit data and can be calibrated, configured or diagnosed directly from a PLC or computer system. No intermediate analyzer boxes are necessary. AnalogPlus sensors and analyzers are used in more conventional analytical measurement



applications.

Online/ Process pH/ORP Electrodes		
EC100GTSO05B	Ryton-body pH combination electrode with Pt 100 RTD (ATC) with 5m connecting cable with BNC and connector for PMP and Pt 100	P.O.R
EC100GTSO10B	Ryton-body pH combination electrode with Pt 100 RTD (ATC) with 10m connecting cable with BNC and connector for PMP and Pt 100	P.O.R
EC100GTSO20B	Ryton-body pH combination electrode with Pt 100 RTD (ATC) with 20m connecting cable with BNC and connector for PMP and Pt 100	P.O.R
ECARTSOHF05B	Ryton-body pH combination electrode without ATC with 5m connecting cable with BNC connector. HF resistant glass. Ideal for application having hydrofluoric acid	P.O.R
ECARGTSO05B	Ryton-body pH combination electrode without ATC with 5m connecting cable with BNC and connector for PMP	P.O.R
ECARHTTSO05B	Ryton-body pH combination electrode without ATC with 5m connecting cable with BNC Connector. High temperature applications up to 110 °C	P.O.R
ECARTSO05B	Ryton-body pH combination electrode without ATC with 5m connecting cable with BNC Connector	P.O.R
ECHTAUTSO05B	Ryton-body ORP gold electrode without ATC with 5m connecting cable with BNC and connector for PMP	P.O.R
ECHTPPTS005B	Ryton-body ORP platinum electrode without ATC with 5m connecting cable with BNC and connector for PMP	P.O.R
ECFC7252203B	General purpose plastic-body double junction pH combination electrode, 12x110 mm, 2m cable length (for pH field monitor)	P.O.R
ECFC7252205B	General purpose plastic-body double junction pH combination electrode, 12x110 mm, 5m cable length (for pH field monitor)	P.O.R
ECFC7960202B	General purpose epoxy-body double junction ORP electrode, 12x110 mm, 2m cable length (for ORP field monitor)	P.O.R
ECFC7960205B	General purpose epoxy-body double junction ORP electrode, 12x110 mm, 5m cable length (for ORP field monitor)	P.O.R



Online/Process Conductivity/TDS Electrodes

ECCS10-0-01T	Conductivity/Resistivity electrode with Pt100, cell constant K=0.01, Titanium with 25-feet cable length, tinned open-ended. For ultra-pure water. (with 1/2 Inch nylon plastic cap threading)	P.O.R
ECCS10-0-01TS	Conductivity/Resistivity electrode with Pt100, Cell constant K=0.01, Titanium with 25-feet cable length, tinned open-ended. For ultra-pure water. (with 1/2 inch stainless steel cap threading)	P.O.R
ECCS10-0-01S	Conductivity/Resistivity electrode with Pt100, cell constant K=0.01, stainless steel with 25-feet cable length, tinned open-ended. For pure, boiler feed water, power plant and condensate water. (with 1/2 inch nylon plastic cap threading)	P.O.R
ECCS10-0-01SS	Conductivity/Resistivity electrode with Pt100, Cell constant K=0.01, stainless steel with 25-feet cable length, tinned open-ended. For pure, boiler feed water, power plant and condensate water. (with 1/2 inch stainless steel cap threading)	P.O.R
ECCS10-0-1S	Conductivity electrode with Pt100, cell constant K=0.1, stainless steel with 25-feet cable length, tinned open-ended. For boiler feed water, power plant and condensate water. (with 1/2 Inch nylon plastic cap threading)	P.O.R
ECCS10-0-1SS	Conductivity electrode with Pt100, cell constant K=0.1, stainless steel with teflon insert and 25-feet cable length, tinned open-ended. For boiler feed water, power plant and condensate water. (with 1/2 inch stainless steel cap threading)	P.O.R
ECCS10-0-1SSP	Conductivity electrode with Pt100, cell constant K=0.1, stainless steel with PEEK insert and 25-feet cable length, tinned open-ended. For boiler feed water, power plant and condensate water. (with 1/2 inch stainless steel cap threading)	P.O.R
ECCS10-1-0S	Conductivity electrode with Pt100, cell constant K=1.0, stainless steel with 25-feet cable length, tinned open-ended. For general purpose applications. (with 1/2 inch nylon plastic cap threading)	P.O.R
ECCS10-1-0SS	Conductivity electrode with Pt100, cell constant K=1.0, stainless steel with teflon insert and 25-feet cable length, tinned open-ended. For general purpose applications. (with 1/2 Inch stainless steel cap threading)	P.O.R
ECCS10-1-0SSP	Conductivity electrode with Pt100, cell constant K=1.0, stainless steel with PEEK insert and 25-feet cable length, tinned open-ended. For general purpose applications. (with 1/2 inch stainless steel cap threading)	P.O.R
ECCONSEN88X	Conductivity graphite 2-ring epoxy-body electrode with Pt100, cell constant K=1.0, tinned open-ended, 12 x 110mm, 7.5m cable length. For general purpose applications	P.O.R
ECCONSEN89X	Conductivity graphite 2-ring epoxy-body electrode with Pt100, cell constant K=0.1, tinned open-ended, 12 x 110mm, 7.5m cable length. For general purpose applications	P.O.R



Prices, Models And Specifications Are Subject To Change Without Prior Notice

For P.O.R Range Please Contact Office

***Prices Are Valid Till March 31, 2025 Subject To Revision On Account Of Currency Fluctuation Or Any Other Factor**